



## 01000 Motor Oil 15W-40 Multi Grade

Document version: Apr 22, 2024



### Description

This mineral motor oil has been specially developed for light duty petrol- and diesel engines of passenger cars. This motor oil is not suitable for turbo engines.

### According to the specifications of

API CD / SF / SG  
CCMC D1  
CCMC G2  
Ford M2C9011-A  
GM 6085M  
MIL-L-46152B

### Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
01001	1 L	6	450
01004	4 L	4	112
01005	5 L	4	112
01020	20 L	1	30
01060	60 L	1	6
01205	205 L	1	2
01999	1000 L	1	-
P01000	1 L	1	-

## Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.882	kg/l
Viscosity	15W-40	
Kinematic Viscosity at 40°C	105	mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	14	mm <sup>2</sup> /s
Viscosity Index	135	
Dynamic Viscosity at -20°C	6340	mPa.s
Flashpoint COC	218	°C
Pourpoint	-36	°C
Total Base Number	5.5	mgKOH/g
Sulphated Ash	0.55	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.