



04000HM Motor Oil 10W-40 Semi Synthetic Higher Mileage

Document version: Apr 22, 2024



Description

This motor oil has been specially developed to delay the ageing process and combat leaks through cracked rings, oxidation and a higher fuel consumption in engines with a high mileage and as a result to extend the engine life.

According to the specifications of

API CF / SL

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
04001HM	1 L	6	450
04005HM	5 L	4	112
04020HM	20 L	1	30
04060HM	60 L	1	6
04205HM	205 L	1	2
04999HM	1000 L	1	-
P04000HM	1 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.881	kg/l
Viscosity	10W-40	
Kinematic Viscosity at 40°C	97	mm ² /s
Kinematic Viscosity at 100°C	14.1	mm ² /s
Viscosity Index	150	
Dynamic Viscosity at -25°C	6000	mPa.s
Flashpoint COC	220	°C
Pourpoint	-39	°C
Total Base Number	7.9	mgKOH/g
Sulphated Ash	1	mass%
Noack Evaporation Loss	12.8	mass%

These characteristics are typical of current production. Variations in these characteristics may occur.