



# 14000LS Gear Oil 85W-140 GL-5 Mineral Limited Slip

Document version: Apr 15, 2024



## Description

This mineral SAE 85W-140 Limited Slip gear oil has been specially developed for lubrication of heavy duty hypoid drives in rear axles and in all transmissions where a mineral limited slip oil SAE 85W-140 GL-5 is specified.

## According to the specifications of

API GL-5 Limited Slip  
MIL-L-2105C  
MIL-L-2105D  
ZF TE-ML 05C

## Packaging units

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 14020LS  | 20 L   | 1              | 30               |
| 14060LS  | 60 L   | 1              | 6                |
| 14205LS  | 205 L  | 1              | 2                |
| 14999LS  | 1000 L | 1              | -                |

## Standard analyses

| TEST                | VALUE   | METHOD             |
|---------------------|---------|--------------------|
| Density             | 0.905   | kg/l               |
| Viscosity           | 85W-140 |                    |
| Kinematic Viscosity | 100     | mm <sup>2</sup> /s |
| Viscosity Index     | 86      |                    |
| Flashpoint          | 215     | °C                 |
| Pourpoint           | -18     | °C                 |

These characteristics are typical of current production. Variations in these characteristics may occur.