



36000 STOU 15W-30 GL-4 Multitrac Mineral

Document version: Apr 22, 2024



Description

This mineral STOU (Super Tractor Oil Universal) multitrac SAE 15W-30 multifunctional agricultural oil has been specially developed for use in diesel engines, transmissions, power take-offs, wet brakes, hydraulic systems, power steering and end drive of among others tractors, combines, road and hydraulic engineering machines.

According to the specifications of

API CF-4 / CG-4 / GL-4
Allison C4
Ford M2C134-C / M2C134-D / M2C159-B / M2C159-C / M2C86-A
John Deere J27 / JD14B / JD20A / JD20C
MIL-L-2104D
MIL-L-2105
MIL-L-46152C
Massey Ferguson M-1135 / M-1139 / M-1143 / M-1144
New Holland 030C / 420A
ZF TE-ML 06B / 07B

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
36001	1 L	6	450
36005	5 L	4	112
36020	20 L	1	30
36060	60 L	1	6
36205	205 L	1	2
36999	1000 L	1	-

Standard analyses

TEST	VALUE	METHOD
Density at 15°C	0.877	kg/l
Viscosity	15W-30	
Kinematic Viscosity at 40°C	81.7	mm ² /s
Kinematic Viscosity at 100°C	10.8	mm ² /s
Viscosity Index	118	
Dynamic Viscosity at -20°C	6600	mPa.s
Flashpoint COC	222	°C
Pourpoint	-35	°C
Total Base Number	10.7	mgKOH/g

These characteristics are typical of current production. Variations in these characteristics may occur.