



BLO20000 Marine FC-W Engine Oil 4-Stroke Outboard EHP 10W-30

Document version: Apr 15, 2024



Description

This marine FC-W outboard oil is a four-stroke engine oil based on high quality base oils with special additives. Because of his excellent 'shear stability' in combination with a very strong anti-corrosion, oxidation and wear properties this four-stroke oil is suitable for use in high speed and heavy duty outboard engines as e.g. Mercury engines. This outboard engine oil meets the latest requirements set by the NMMA. The specific marine engine oil is not suitable for use in outboard engines with after treatment system and for us in cars.

According to the specifications of

API SJ / SL
NMMA FC-W

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
BLO20001	1 L	6	450
BLO20005	5 L	4	112
BLO20020	20 L	1	30
BLO20060	60 L	1	6
BLO20205	205 L	1	2
BLO20999	1000 L	1	-
PBL020000	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.871	kg/l	
Viscosity SAE	10W-30 10		
Kinematic Viscosity at 40°C	76.6	mm ² /s	
Kinematic Viscosity at 100°C	11.8	mm ² /s	
Viscosity Index	149		
Dynamic Viscosity at -25°C	5000	mPa.s	
Flashpoint COC	216	°C	
Pourpoint	-27	°C	
Total Base Number	7.7	mgKOH/g	

These characteristics are typical of current production. Variations in these characteristics may occur.