



16000ZF6 ATF Automatic Transmission Fluid M-1375.4

Document version: May 13, 2024



Description

This premium synthetic automatic transmission oil has been specially developed for all 6 speed ZF transmissions and other applications for which manufacturers require an M-1375.4 specification.

According to the specifications of

Aston Martin ATF M-1375.4
BMW 83 22 0 142 516 / 83 22 2 305 396
Bentley PY112995PA
Hyundai 0400000C90SG
Jaguar ATF M-1375.4 / Fluid 8432
Land Rover TYK 500050
Maserati 231603 / Gran Turismo ATF M-1375.4 / Quattroporte ATF M-1375.4
Porsche ATF M-1375.4
Rolls Royce ATF M-1375.4
VW G 055 005

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
16001ZF6	1 L	6	450
16004ZF6	4 L	4	112
16020ZF6	20 L	1	30
16060ZF6	60 L	1	6
16205ZF6	205 L	1	2
16999ZF6	1000 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.845	kg/l	
Colour	brown		
Viscosity	10W		
Kinematic Viscosity at 40°C	26.8	mm ² /s	
Kinematic Viscosity at 100°C	5.6	mm ² /s	
Viscosity Index	151		
Flashpoint COC	210	°C	
Pourpoint	-51	°C	
Brookfield Viscosity at -40°C	8500	mPa.s	

These characteristics are typical of current production. Variations in these characteristics may occur.